

INSTALLATION GUIDELINES for U-Glue Digital Wallpaper™

SURFACE PREPARATION

- Wall should be prepped to a smooth, clean and dry surface prior to installation. Blue River Digital wallpaper will not hide wall flaws such as nail holes, bumps or dirt.
- Primer sealer should be used on unpainted drywall. Use an acrylic wallcovering primer, such as:
 - Professional Ultra Prime Pro-977
 - Golden Harvest White Bite
 - Allpro Ultra Prep 685
- Priming provides a sound surface to which wallcovering will adhere. It is recommended to strip down previous layers of wallcovering if present. The old wallcovering may appear to be firmly adhered to the wall, but the addition of another layer can cause adhesion failure.
- Prime over glossy paint with one of the above-named primers.

ADHESIVE INFORMATION

- Use one of these clear adhesives to provide good adhesion and allow for easier stripping when the wall covering is to be removed or replaced:
 - Professional Ultra Premium Heavy Duty Clear Strippable Pro-880
 - Golden Harvest GH-34 Clear Strippable
 - Allpro Pro-Duty 3400
- The following clay adhesives have also been shown to be effective both during installation and removal of Blue River Digital wallpaper:
 - Professional Extra Strength Pro-732
 - Professional Clay Strippable Pro-774
 - Golden Harvest GH-40
 - Allpro Extra Strength Vinyl 600
 - Allpro Clay Strippable 661
- For more permanent applications, use one of these pastes which yield a more aggressive adhesion:
 - Professional Heavy Duty Clear Pro-838
 - Allpro Clear Hang 610
- Vinyl over vinyl pastes tend to dry too quickly on these products and are not recommended.
- Apply a coat of the adhesive using a ½” nap paint roller. Book for 10 minutes.

HANGING INSTRUCTIONS

- Do not use tape on imaged surface.
- Align top and adjoining edges. Smooth panels into place with a smoothing brush, starting at the center of the panel working toward the edges.
- Use a plastic smoother to push air pockets to the edges.